

Page 1/10

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025

Reviewed on 05/15/2025

Tel.: +49 (0)800 4372522

1 Identification

- · Product identifier
 - · Trade name: Paladon 65 liquid

- · Application of the substance / the mixture Manufacture of dental prothesis
- · Details of the supplier of the safety data sheet
 - · Manufacturer/Supplier:

Kulzer GmbH

Leipziger Straße 2, 63450 Hanau (Germany)

Information department:

Tel. +1 (800) 431-1785 Fax: +1 (800) 522-1545 e-mail: customer.servicehkna@kulzer-dental.com

· Emergency telephone number:

Emergency CONTACT (24-Hour-Number)
ID 105860: (domestic) 1 800 535 5053 or international (001) 352 323 3500

2 Hazard identification

Classification of the substance or mixture

Flammable Liquids - Category 2 Skin Irritation - Category 2 Skin Sensitizer - Category 1

Reproductive Toxicity - Category 2

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure - H335 May cause respiratory irritation. Category 3

· Label elements

GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms







GHS02 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labeling:

methyl methacrylate p-Mentha-1,4-diene

Tetramethylene dimethacrylate

· Hazard statements

Highly flammable liquid and vapour.

Causes skin irritation.

May cause an allergic skin reaction.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.

(Contd. on page 2)



Page 2/10

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025 Reviewed on 05/15/2025

Trade name: Paladon 65 liquid

· Precautionary statements

(Contd. of page 1)

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/fume/gas/mist/vapours/spray.

Wear protective gloves / eye protection.

Wear protective clothing.

If skin irritation or rash occurs: Get medical advice/attention.

· Classification system

NFPA ratings for USA (scale 0-4)



Health = 2 Fire = 3 Reactivity = 2

· HMIS-Ratings (Scale 0-4)



Health = 2 Fire = 3 Reactivity = 2

· Other hazards -

3 Composition/Information on ingredients

· Chemical characterization: Mixtures

· **Description:** Composition based on methacrylates

· Danger	ngerous components:				
	methyl methacrylate Flammable Liquids - Category 2, H225 Skin Irritation - Category 2, H315; Skin Sensitizer - Category 1, H317; Specific Target Organ Toxicity - Single Exposure - Category 3, H335	>90% w/w			
2082-81-7	Tetramethylene dimethacrylate Skin Sensitizer - Category 1B, H317	≥1-≤5% w/w *			
	p-Mentha-1,4-diene Flammable Liquids - Category 3, H226 Reproductive Toxicity - Category 2, H361	≥0,1-<0,2% w/w *			

^{*} Actual concentration ranges are withheld as a trade secret.

4 First-aid measures

- · Description of first aid measures
 - · After inhalation Supply fresh air; consult doctor in case of complaints.
 - · After skin contact Immediately wash with water and soap and rinse thoroughly.
 - · After eye contact Rinse opened eye for several minutes under running water.
 - · After swallowing

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

(Contd. on page 3)

[·] Additional information For the wording of the listed hazard phrases refer to section 16.



Page 3/10

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025 Reviewed on 05/15/2025

Trade name: Paladon 65 liquid

(Contd. of page 2)

- · Information for doctor
 - · Most important symptoms and effects, both acute and delayed No further relevant information available.
 - · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
 - Suitable extinguishing agents CO2, sand, extinguishing powder. Do not use water.
 - For safety reasons unsuitable extinguishing agents Water.
- Special hazards arising from the substance or mixture

Can form explosive gas-air mixtures.

Formation of toxic gases is possible during heating or in case of fire.

- · Advice for firefighters
 - · Protective equipment: No special measures required.
- · Additional information -

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
 - Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Prevent seepage into sewage system, workpits and cellars.
- Methods and material for containment and cleaning up:

Absorb with liquid binding material (diatomite, universal binders, for small amounts tissues).

Do not flush with water or aqueous cleansing agents

Send for recovery or disposal in suitable receptacles.

- Reference to other sections
- See Section 13 for disposal information.

See Section 8 for information on personal protection equipment.

-

7 Handling and storage

- · Handling
 - Precautions for safe handling

Keep receptacles tightly sealed.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
 - · Storage
 - · Requirements to be met by storerooms and receptacles: Store in a cool location.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:

Keep cool, if possible (not above 25 °C).

(Contd. on page 4)



Page 4/10

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025 Reviewed on 05/15/2025

Trade name: Paladon 65 liquid

(Contd. of page 3)

Store in cool, dry conditions in well sealed receptacles.

Specific end use(s) No further relevant information available.

8 Exposure controls/ Personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
 - · Components with limit values that require monitoring at the workplace:

80-62-6 methyl methacrylate

EL STEL: 100 ppm TWA: 50 ppm

S(D)

TWA: 50 ppm

· Additional information: The lists that were valid during the creation were used as basis.

- · Exposure controls
 - Personal protective equipment
 - General protective and hygienic measures

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Not necessary with efficient local exhaust. If exposition to vapours is possible, use breathing protective mask (filter A).

Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

If skin contact cannot be avoided, protective gloves are recommended to avoid possible sensitization.

Solvent resistant gloves

Check protective gloves prior to each use for their proper condition.

recommended

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR Nitrile rubber, NBR

(Contd. on page 5)



Page 5/10

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025 Reviewed on 05/15/2025

Trade name: Paladon 65 liquid

(Contd. of page 4)

· Eye protection: Tightly sealed goggles. · Body protection: Light weight protective clothing

Information on basic physical and che	formation on basic physical and chemical properties		
General Information	, , , , , , , , , , , , , , , , , , ,		
· App <u>e</u> arance:	F1 : 1		
· Form: · Color:	Fluid Colorless		
Odor:	Ester-like		
· Odor threshold:	Not determined.		
· pH-value:	Mixture is non-soluble (in water).		
· Change in condition			
· Melting point/Melting range:	-48 °C (-54,4 °F)		
Boiling point/Boiling range:	100,3 °C (212,5 °F)		
· Flash point:	11,5 °C (52,7 °F)		
· Flammability (solid, gaseous)	Not applicable.		
· Auto igniting:	430 °C (806 °F)		
· Decomposition temperature:	Not determined.		
· Ignition temperature:	Product is not selfigniting.		
· Danger of explosion:	Product is not explosive. However, formation of explosiv air/vapor mixtures are possible.		
· Explosion limits:			
·Lower:	2,1 Vol %		
· Upper:	12,5 Vol %		
· Vapor pressure at 20 °C (68 °F):	47 hPa (35,3 mm Hg)		
· Density at 20 °C (68 °F):	0,940 g/cm³ (7,8443 lbs/gal)		
Relative density	Not determined.		
Vapor density	Not determined.		
Evaporation rate	Not determined.		
Solubility in / Miscibility with	And the state of t		
Water:	Not miscible or difficult to mix		
· Partition coefficient (n-octanol/water): Not determined.			
· Viscosity:			
dynamic at 20 °C (68 °F):	1 mPas		
· kinematic:	Not determined.		
Other information	No further relevant information available.		



Page 6/10

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025

Reviewed on 05/15/2025

Trade name: Paladon 65 liquid

(Contd. of page 5)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Possibility of hazardous reactions No dangerous reactions known
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- Hazardous decomposition products: none
- · Additional information:

Product might polymerize after considerable exceeding of recommended storage time or temperature.

11 Toxicological information

- · Information on toxicological effects
 - · Acute toxicity:

Acute toxicity.			
· LD/LC50 values that are relevant for classification:			
80-62-6 m	ethyl met	hacrylate	
Oral	LD50	~7.900 mg/kg (rat) weight of evidence	
Dermal	LD50	>5.000 mg/kg (guinea pig) (OECD 402)	
Inhalative	LC50/4 h	29,8 mg/l (rat)	
2082-81-7 Tetramethylene dimethaci		hylene dimethacrylate	
Oral	LD50	10.066 mg/kg (rat) (OECD 401)	
99-85-4 p-Mentha-1,4-diene		.4-diene	
Oral	LD50	>2.000 mg/kg (rat) (OECD 423)	
Dermal	LD50	>2.000 mg/kg (rat) (OECD 402)	

- · Primary irritant effect:
 - on the skin: Irritant to skin and mucous membranes.
 - · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
80-62-6 methyl methacrylate	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	

· Reproductive toxicity Based on available data, the classification criteria are not met.

CA

(Contd. on page 7)



Page 7/10

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025 Reviewed on 05/15/2025

Trade name: Paladon 65 liquid

(Contd. of page 6)

2 Ecological information					
· Toxicity					
· Aquatic t	· Aquatic toxicity:				
80-62-6 meth	nyl methacrylate				
EC50/21d	49 mg/L (daphnia) (OECD 211)				
EC50/48h	69 mg/l (daphnia) (EPA OTS 797.1300)				
NOEC / 21d	37 mg/l (daphnia) (OECD 211)				
ErC50 / 72 h	>110 mg/l (algae) (OECD 201)				
NOEC / 72h	110 mg/l (algae) (OECD 201)				
NOEC / 48h	48 mg/l (daphnia) (EPA OTS 797.1300)				
EbC50 / 72h	>110 mg/l (algae) (OECD 201)				
NOEC/ 35d	9,4 mg/L (fish) (OECD 210)				
LC50/ 35d	33,7 mg/L (fish) (OECD 210)				
	etramethylene dimethacrylate				
	14,1 mg/L (daphnia) (OECD 211)				
	32,5 mg/l (fish)				
	5,09 mg/l (daphnia) (OECD 211)				
	9,79 mg/l (algae) (OECD 201)				
	2,11 mg/l (algae) (OECD 201)				
	25 mg/l (fish)				
ErC10/72h	, , , ,				
	entha-1,4-diene				
EC50/72h	>10,82 mg/l (algae) (OECD 201)				
EC50/48h	10,189 mg/l (daphnia) (OECD 202)				
LC50/96h	2,792 mg/l (fish) (OECD 203)				
	and degradability				
	80-62-6 methyl methacrylate				
	biodegradability 94 % /14d (not defined) (OECD 301C)				
	2082-81-7 Tetramethylene dimethacrylate				
	biodegradability 84 % /28d (not defined) (OECD 310)				
99-85-4 p-Mentha-1,4-diene					
biodegradabi	biodegradability 27 % /28d (not defined) (OECD 301F; ISO 9408/ EEC 92/69/V, C.4-D)				

- Behavior in environmental systems:
 - · Bioaccumulative potential No further relevant information available.
 - · **Mobility in soil** No further relevant information available.
- Additional ecological information: General notes:

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
 - · **PBT:** Not applicable.

(Contd. on page 8)



Page 8/10

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025

Reviewed on 05/15/2025

Trade name: Paladon 65 liquid

(Contd. of page 7)

· **vPvB:** Not applicable.

Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
 - · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

- · Uncleaned packagings:
 - · Recommendation:

Disposal must be made according to official regulations. Non contaminated packagings can be used for recycling.

· UN-Number

· **DOT/TDG, ADR, IMDG, IATA** UN1247

· UN proper shipping name

· DOT/TDG

· ADR

· IMDG, IATA

Methyl methacrylate monomer, stabilized solution 1247 Methyl methacrylate monomer, stabilized solution

METHYL METHACRYLATE MONOMER,

STABILIZED solution

- · Transport hazard class(es)
 - DOT/TDG (Transport dangerous goods):



· Class

Label

3 Flammable liquids

3

· ADR



· Class

3 (F1) Flammable liquids

(Contd. on page 9)



Page 9/10

(Contd. of page 8)

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025 Reviewed on 05/15/2025

Trade name: Paladon 65 liquid

·Label · IMDG, IATA 3 Flammable liquids · Class · Label · Packing group DOT/TDG, ADR, IMDG, IATA II· Environmental hazards: Marine pollutant: No Warning: Flammable liquids · Special precautions for user · Hazard identification number (Kemler code): 339 · EMS Number: F-E,S-D · Stowage Category Stowage Code SW2 Clear of living quarters. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · ADR Excepted quantities (EQ)

· IMDG

Limited quantities (LQ)

Excepted quantities (EQ)

1L

Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500

Maximum net quantity per outer packaging: 500

mı

· UN "Model Regulation":

UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED SOLUTION, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 - · Sara

SARA Section 355 (extremely hazardous substances)

None of the ingredients is listed.

(Contd. on page 10)



Page 10/10

Safety Data Sheet according to HPR, Schedule 1

Printing date 05/15/2025 Reviewed on 05/15/2025

Trade name: Paladon 65 liquid

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H315 Causes skin İrritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

· Date of the latest revision of the safety data sheet 05/15/2025 / 3

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

IMDG. International Mantime Code for Dangerous Goods
DOT: US Department of Transportation
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

* Data compared to the previous version altered.